

TECHNICAL DATA SHEET
DESCRIPTION

A-20 is a fire retardant, woven HDPE scrim with a polyethylene coating on both sides. Meets or exceeds NFPA 701 LS/SM.

PHYSICAL PROPERTIES AND TYPICAL VALUES

PROPERTY	ASTM TEST METHOD	U.S. VALUE	METRIC VALUE
Weight	D-2103	37 LB/1000 FT ²	18.1 KG/100 M ²
Thickness	D-2103	10 MIL	0.254 MM
Tensile Strength	D-5034	165 LBF	734 N
Tongue Tear	D-2261	62 LBF	276 N
Trapezoidal Tear	D-4533	46 LBF	205 N
PPT Resistance	D-2582	30 LBF	133 N
Flammability	CPAI 84 Sec. 6	Meets or exceed requirements	
	CPAI 84 Sec. 7	Meets or exceed requirements	

AVAILABLE COLORS

Yellow or Green

OUR CUSTOMERS DON'T JUST *cover their business,*
➔ THEY PROTECT IT



REEF INDUSTRIES, INC.
 9209 Almeda Genoa Rd. • Houston, Texas 77075
 P: 713.507.4251 • F: 713.507.4295
 E-mail: ri@reefindustries.com • www.reefindustries.com

TOLLFREE 1.800.231.6074

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, expressed or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.